

## Sieg iKC6



### Specifications

|                                |                  |
|--------------------------------|------------------|
| Turning diameter over bed(max) | 300mm            |
| Travel across slide            | 100mm            |
| Center width                   | 400mm            |
| Chuck diameter                 | 125mm            |
| Spindle speed                  | 100-3000r/min    |
| Spindle through-hole           | 20mm             |
| Spindle mount                  | MT3              |
| Spindle motor power            | 1500W            |
| X travel                       | 240mm            |
| Z travel                       | 320mm            |
| The max moving speed           | 5000mm/min       |
| The max feeding speed          | 1000mm/min       |
| Motor                          | 400w             |
| Tool position                  | 8                |
| Tool dimension internal        | Ø 10mm           |
| Tool dimension external        | 10*10mm          |
| Tailstock taper                | MT2              |
| Tailstock sleeve diameter      | 17mm             |
| Travel of tailstock            | 50mm             |
| Positioning accuracy           | 0.005mm          |
| Repeatability accuracy         | 0.005mm          |
| Power                          | 230Vac           |
| Weight (NW/GW)                 | 620/700kg        |
| Overall dimension              | 1400×770×1600mm  |
| Packing size                   | 1650x1090x1920mm |

Specifications subject to change without notice.

Picture may vary from actual machine.

© 2017